

Ecoplat

Semi-Automatic Stretch Wrapper

The Ecoplat semi-automatic turntable stretch wrapper wraps up to 25 loads per hour. This pallet wrapper is R-connect ready, which allows you to monitor and improve your packaging performance through remote assistance.



PERFORMANCE	
Production Rate	Up to 25 loads per hour
Turntable Weight Capacity	4,400 lbs (standard), 5,500 lbs (optional)
Maximum Load Dimension	40" (L) x 48" (W) x 86" (H)/110" (H)
Temperature Operating Range	Between 41°F and 104°F
WRAPPING	
R-Connect Ready	Remote Machine Monitoring and Film Consumption Tracking. Eliminate Downtime by Troubleshooting your Machines. Programmed Diagnostic: 24 hours a day, 7 days a Week.
Load Height Sensing	Automatic Height Detection via Photocell for Light Loads
OPERATOR INTERFACE	
Control Panel	LED Display and JOG Dial Programmable Selector
Wrapping Menus	3 Fixed Menus and 1 Operator Programmable Menu
E-Stop	Emergency Stop on Control Panel
Film Carriage Speed and Positioning	Variable Up/Down, with Manual Up/Down Jog Capability
Wrap Counters	Top/Bottom separately, and Reinforcement Wraps
Turntable Speed	4-10 rpm
TURNTABLE DESIGN	
Turntable Size	65"
Turntable Top Thickness	3/8" thick Diamond-Shaped plated Steel
Turntable Support	28 x 1-5/8" UHMW covered support casters
Turntable Drive	1 HP VAC, Heavy Duty Chain and Sprocket Drive
MAST	
Effective Load Wrap Height	86"/110"
FILM DELIVERY	
Film Delivery System	Frictioned Roller Device (FRD) with Core Breaker
Wrap Patterns	Customizable with up to 5 Programs
FILM CARRIAGE	
Film Carriage	20"W (standard)
Film Threading	Patented S Pattern, with advanced grip
Film Thickness	39 to 138 gauges
WARRANTY	
Machine Warranty	3 years

ELECTRICAL DATA	
Electrical Requirements	120V, 10A, 50Hz, 1-phase
MACHINE DIMENSIONS	
Installed Dimensions	104" (L) x 71" (W) x 103" (H)/127" (H)
Shipping Dimensions	126" (L) x 89" (W) x 28" (H)
Shipping Weight	1,276 lbs
MACHINE CONSTRUCTION	
Base Fabrication	Cold formed steel frame
Fork Truck Portability	Front and rear
Mast Construction	Cold formed steel with rounded corners

Protect your Operator and Machine

ECOPLAT CHARACTERISTICS	
NEMA 13	Protection from dirt, spraying water, noncorrosive coolants
Chain Safety	Patented Anti-Fall Clamp Device
Operator Protection	A safety distance of 23" between fixed and moving parts
Safety and Electrical Compliance	CE compliant, UL Ready
Manufacturing Certification	ISO 9001

